

TECHNICAL DATA SHEET

TEL

EkoStripper

Technical characteristic

sec. 1

EKOSTRIPPER is a special stripper for removing any kind of paint from every surface. The product can strip more coats of paint when left on the surface for the required time. The lack of odours and dangerous emissions even allow its use indoors, without the need for special ventilation. It is odourless, non-toxic, non-flammable and environment friendly.

Ideal use

sec. 2

Interior and exterior surfaces.

Application method

sec. 4

Apply EKOSTRIPPER by using a brush or spatula and wait 1 to 24 hours according to the coats of paint to be removed. The product does not trickle, therefore it can be spread also on vertical surfaces. With a spatula or a scraper, remove both EKOSTRIPPER and the stripped paint, then clean the treated surface with water.

Technical characteristics : the application

sec. 6

Dilution / Mixing	Ready to use
Yield	2 ÷ 3 m ² /l for enamels and smooth paints, 1 ÷ 2 m ² /l for thick products
Application tools	Brush, trowel
Application temperature	5°C ÷ +36°C (with relative humidity not higher than 80%)
Tools cleaning	Water

Technical characteristics : the product

sec. 7

Composition	Mix of water and environment friendly agents with high boiling point components.
Specific weight	0.97 kg/l +/- 3% (white)
pH	7
Viscosity	25,000 +/-5% CPS Brookfield (RVT 20 revs/min. a 25°C)
Storage temperature	+2°C ÷ +36°C. Keep from freezing
Reaction to fire	None if applied on to non-flammable surfaces: water-based material with dry thickness less than 0.600 mm
Colour	Semi-transparent green
Packaging	0,75 – 4 – 14 l

Toxicological data

sec. 8

The product is free of any harmful substances, pigments or other components containing heavy metals such as lead or chrome. Further to this, the product contains no toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. The product is non combustible and is held to be a non-toxic substance if used in the technically correct manner. Normal cautionary measures for the handling of water based paints are advised. No special arrangements are required for the storage, movement and transportation of the product, any spillage should be cleaned up using absorbent inert material such as sand, soil etc. and then disposed of as any normal waste product according to national and regional current regulations. The transportation must be carried out in conformity with international agreements

Specification

sec. 9

Apply one coat of a special stripper such as EKOSTRIPPER by OIKOS by using a brush or spatula and wait according to the coats of paint to be removed. The product does not trickle; therefore it can be spread also on vertical surfaces. With a spatula or a scraper, remove both the stripper and the stripped paint, then clean the treated surface with water. All must be carried out following closely all application instructions, cost per m² including application and materials. Scaffolding not included.