

# TECHNICAL DATA SHEET

## TDL

### Nevada

#### sez. 1.0 Technical characteristic

**NEVADA la Pintura Dorada** is a decorative paint that unifies colours, contrasts and golden shimmers and brings to the wall an enchanting appearance. Thousands of tiny drops of paint that are broken by the passing of a trowel and that due to a particular magnetism, become a blend of colours with a golden touch. Thanks to its formulation and the special pigments used, it is possible to admire the numerous shades of colour that are able to bring new sensations to walls, from a golden amber to beautiful golden shimmers that give precious reflections to an ambiance.

**NEVADA la Pintura Dorada** is washable, waterproof, scratch proof and helps to prevent the formation of mould. It is particularly indicated for the decoration of surfaces in prestigious environments such as villas, palaces, offices, high class studios, apartments and elegant boutiques and shops. Easy to apply, NEVADA allows application without leaving joints or imperfections. The product is free of toxic substances. The product does not contain toxic solvents, odours or chlorides. Friendly both to humans and the environment

#### sez. 2.0 Ideal Use

Interior surfaces in every type of building both historic and modern.

#### sez. 3.0 Surface preparation

New surfaces should be dry and thoroughly mature. On old surfaces or previously painted surfaces, remove deposits of dust, smog or other impurities by brushing or washing. Remove any loose or crumbling material. Follow this by applying, if necessary, a coat of the special sealer NEOFIX by OIKOS. Wait 4 ÷ 6 hours until dry. Apply one or two coats of FONDO MURALES by OIKOS as a base coat. Wait 6 ÷ 8 hours until dry.

#### sez. 4.0 Application method

Apply **Nevada la Pintura Dorada** by the special Spanish-Brush by OIKOS crossing the brush strokes, immediately pass over the same part of the surface with the Spanish-Brush empty, in order to evenly distribute the product over the surface. After 5 ÷ 10 minutes pass over the surface again with an inox steel trowel by OIKOS, applying light pressure to squash the product but without removing it.

#### Technical characteristics: the application

sec. 6

Dilution	5 ÷ 10% drinkable water
Yield	6 ÷ 8 m <sup>2</sup> /l depending on the method used in application
Application tools	Spanish-Brush and inox steel trowel by OIKOS
Fixatives	NEOFIX by OIKOS
Base Coats	FONDO MURALES by OIKOS
Application temperature	+5°C ÷ +36°C (with relative humidity not exceeding 80%)
Drying time: touch dry	3 ÷ 4 hour (temperature = +20°C with relative humidity not exceeding 75%)
Drying time: fully cured	2 ÷ 3 days (temperature = +20°C with relative humidity not exceeding 75%)
Tools cleaning	Water
Warning	hand mix or in gyroscopic mixer for max. 1 minute low speed.

#### Technical characteristics: the product

sec. 7

Composition	acrylic resins in water dispersion, organic and inorganic pigments with golden effect.
Specific weight	1,00 kg/l +/- 3%
pH	6 ÷ 7
Viscosity	7.500 ÷ 11.500 CPS Brookfield (RVT 20 revs/min. a 25°C)
Storage temperature	+2°C ÷ +36°C. Keep from freezing
Fire reaction	negative if the product is applied onto a non-flammable surface: water based material with dry thickness of less than 0.600 mm
Washed resistance	Washable according to the norm UNI 10560:1996
Colours:	shades of the colour chart on the DCS tinting system Decor Color System by OIKOS
Packaging	1 – 5 litres

#### sez. 8.0 Toxicological data

The product is free of any harmful substances, pigments or other components containing heavy metals such as lead or chrome. Further to this, the product contains no toxic solvents, aromatics or chlorides. There is no risk of any dangerous polymerisation. The product is non combustible and is held to be a non-toxic substance if used in the technically correct manner. Normal cautionary measures for the handling of water based paints are advised. No special arrangements are required for the storage, movement and transportation of the product, any spillage should be cleaned up using absorbent inert material such as sand, soil etc. etc. and then disposed of as any normal waste product. . The transport must be executed according to the international agreements

#### Specifications

sec. 9

New surfaces should be dry and thoroughly mature. On old surfaces or previously painted surfaces, remove deposits of dust, smog or other impurities by brushing or washing. Remove any loose or crumbling material. Follow this by applying, if necessary, a coat of the special sealer NEOFIX by OIKOS. Wait 4 ÷

## Technical Data Sheet TDL/do/02

6 hours until dry. Apply one or two coats of FONDO MURALES by OIKOS as a base coat. Wait 6 ÷ 8 hours until dry. Apply **Nevada la Pintura Dorada** by the special Spanish-Brush by OIKOS crossing the brush strokes, immediately pass over the same part of the surface with the Spanish-Brush empty, in order to evenly distribute the product over the surface. After 5 ÷ 10 minutes pass over the surface again with an inox steel trowel by OIKOS, applying light pressure to squash the product but without removing it. All must be carried out in accordance with the norms of application, at a cost of ..... m2. inclusive of materials and labour.